



Paige Plus LED Cable

LED sign wire UL listed wet/sunlight resistant
CM/CL3/PLTC

Connecting you to more.



PART# 984122C (250 ft)
984122M (1,000 ft)

1.0 APPLICATION

- 1.1 LED Wire: 2 Conductor, 12 AWG stranded tinned copper conductor with a sunlight resistant jacket overall 105°C FT-4. Made in USA.

2.0 CONSTRUCTION

2.1 CONDUCTOR

- 2.1.1 Material: Tinned Copper
- 2.1.2 Size: 12 AWG
- 2.1.3 Construction: Stranded

2.2 INSULATION

- 2.2.1 Material: Paige Compound #103184
- 2.2.2 Wall Thickness: .020"
- 2.2.3 O.D.: .132" nom.
- 2.2.4 Color Code: Black and Red

2.3 CABLING OVERALL LAY

- 2.3.1 3" left hand lay

2.4 NOMINAL CABLING DIAMETER

- 2.4.1 .264"

2.5 JACKET

- 2.5.1 Material: Sunlight Resistant Compound
- 2.5.2 Wall Thickness: .045" nom.
- 2.5.3 O.D.: .350" ± .030"

- 2.5.4 Marking: Cable permanently identified via surface inkjet print PAIGE PLUS LED CABLE P/N (* see below) 12AWG 2C E191597 105°C (UL) PLTC OR CL3 SUN RES DIR BUR OR CIC C(UL) PVC 90°C DRY 75° C WET 300V SUN RES FT-4 "SUITABLE FOR WET LOCATIONS OR OUTDOOR USE" "ROHS COMPLIANT" MADE IN USA WWW.PAIGESIGNWIRE.COM

- 2.5.5 Color: Black

2.6 TEMPERATURE/VOLTAGE

- 2.6.1 105°C / 300V

3.0 PACKAGING

- 3.1 P/N 984122C - 250 ft. 1 Pac Boxes and P/N 984122M - 1,000 ft. reels



200 Sheffield Street, Suite 302, Mountainside NJ 07092



908-687-7810
800-327-2443



paigesignwire.com
team@paigesignwire.com

RoHS
UL E191597