

# PLENUM + LED SIGN WIRE SUNLIGHT RESISTANT CL3P

## SPEC

98P183M 1000 ft.  
98P183L 500 ft.  
98P183B 200 ft.



Application: Plenum LED Sign Wire, 2 conductor 18 AWG stranded tinned copper 75°C (UL) CL3P FT-6 Made in USA



## Rip Strip



**RoHS**



### 1.0 CONSTRUCTION

#### 1.1 CONDUCTOR:

- Material: Tinned Copper
- Size: 18 AWG
- Stranding: 16 Strands

#### 1.2 LAY LENGTH:

- This is an integral construction cable

#### 1.3 JACKET:

- Material: Paige Compound #12056
- Wall Thickness: .020"
- O.D.: .187" x .086"
- Marking: "PAIGE WEATHER RESISTANT RIPSTRIP® LED PLENUM + P/N (\*SEE BELOW) CONDUIT NOT REQUIRED E191597 18AWG 2C 75°C (UL) CL3P SUNLIGHT RESISTANT FT-6 "ROHS COMPLIANT" MADE IN USA WWW.PAIGECONNECTED.COM" (sequential footage markers)  
\*98P183M – 1,000 ft. reel  
98P183L – 500 ft. box  
98P183B – 200 ft. bagged
- Color: Light Blue + Light Blue/Red

#### 1.4 TEMPERATURE / VOLTAGE:

- 75°C / 300V

#### 1.5 PACKAGING:

- P/N 98P183M – 1000 ft. reel
- P/N 98P183L – 500 ft. box
- P/N 98P183B – 200 ft. bagged

#### 1.6 STANDARD:

- NEC/UL compliant for all applications other than "Wet" (direct exposure to the elements)

