



# Primary Underground Distribution (URD) Cable



AL Conductor XLPE Insulated 35kV UL 1072

URD cable, rated MV105°C (wet and dry) Flame-retardant Cross-Linked Polyethylene XLPE insulation

Description	Units	Value
Insulation material	XLPE	
Conductor type (Three / Single)	Single	
Conductor Cross-Section	kcmil	1000
Rating / Insulating level	100% or 133%	100%
Approx. Weight/Foot (K)	Lbs	2454
Number of strands of conductor and diameter	#/awg	61/Compress
Standing Class	Class B(Compress)	
Outside Diameter (OD) conductor	inches	1.098
Layer thickness semi-conducting (inner)	ICEA /inches	1.170
Insulation thickness	ICEA /inches	0.345
Layer thickness semi-conducting (outer)	ICEA /inches	1.980
Concentric neutrals (1/3)	No/AWG	29/16AWG
Concentric neutrals (1/2)	No/AWG	23/12AWG
Concentric neutrals (2/3)	No/AWG	22/10AWG
Concentric neutrals (Full)	No/AWG	N/A
Jacket thickness	inches	0.083
Jacket Color	Black/Red Stripes	
Jacket type	LLDPE/XLPE	XLPE

Description	Units	Value
Cable Diameter	inches	2.106
Service temperature rating	Deg/C	105°C
DC Resistance at 20 Deg C	ohms/1000 ft	0.0177
AC Resistance at 105 Deg C	ohms/1000 ft	0.0244
Capacitance	µF//1000ft	0.0903
Inductance	mH/1000ft	0.101
Minimum bending radius	inches	23.1
Maximum pulling tension	Lbs	6000
Ampacity of conductor (conduit in air at 20°C)	Amps/NEC 2020	729
Ampacity of conductor (underground duct at 20°C)	Amps/NEC 2020	565
Ampacity of conductor (cable tray at 40°C)	Amps/NEC 2020	780
Ampacity of conductor (conduit in air at 40°C)	Amps/NEC 2020	640
Short circuit rating of conductor	(Is, kA)	44.4
Standard for ampacity calculation	NEC	NEC
Packing	Wood/Metalsheath	Wood
Reactance** - Duct	Ω/1000ft	0.038
Reactance** - Direct Buried	Ω/1000ft	0.071

\*\*In duct: Triplex, In direct buried: Spaced 7.5 inches horizontal

### Industry Standards

ICEA S-94-649 – Standard for Concentric Neutral Cables Rated 5 through 46 KVA  
 ICEA CSB – Specification for Extruded Dielectric, Shielded Power Cables Rated 5 through 46 KV  
 UL 1072 – Medium-Voltage Power Cables

### Component Standards

ASTM B 231 – Standard Specification for Concentric-Lay-Stranded Aluminum 1350 Conductors  
 ASTM B 3 – Standard Specification for Soft or Annealed Copper Wire  
 ICEA T-31-610 – Test Method for Conducting Longitudinal Water Penetration Resistance Tests  
 ASTM B 5 – Standard Specification for High Conductivity Tough-Pitch Copper Refinery Shapes  
 NEC-National Electric Codebook 2020

**We want to hear from you!**

13111 Atlantic Blvd Suite 3, Jacksonville, FL 32225

Tel: 800.997.2443    [dpritchard@paigeconnected.com](mailto:dpritchard@paigeconnected.com)  
[www.paigeconnected.com](http://www.paigeconnected.com)

